

UNITED STATES PATENT APPLICATION

OF

STEVEN L. EDWARDS

ROBERT MARINACK

JEFFREY McDOWELL

AND

GARY WORRY

FOR

**METHOD FOR MAXIMIZING WATER REMOVAL IN A PRESS NIP**

0  
1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177

RELATED CASES

ing  
This application is a continuation-in-part of copending application Serial No.  
09/191,376, filed November 13, 1998.

FIELD OF INVENTION

10  
15  
20  
The invention relates to a method for maximizing water removal from an absorbent paper web in a press nip. More particularly, the present invention relates to the use of a shoe press on the Yankee dryer with a pressure profile that maximizes water removal. Still more particularly, the present invention relates to a method for utilizing a very steep pressure drop at and/or following the exit of a nip curve in order to maximize water removal by minimizing rewet. Finally, the present invention relates to a method for increasing paper machine speed by utilizing a press section that maximizes water removal.

BACKGROUND OF THE INVENTION

25  
In modern society, bath tissue, paper towels, facial tissue, and paper napkins (hereinafter referred to as packaged paper products) have been remarkably successfully consumer products. The success of these paper products stems from the ability of manufacturers to consistently enhance product attributes at lower cost and to meet volume demands on a timely basis. Packaged paper products offer consumers

5 an array of attributes necessary to such jobs as performing the daily tasks of wiping up  
spills, personal cleansing, and cleaning household goods. For example, paper towels  
are engineered to be absorbent and strong while wet whereas bath tissue products are  
expected to be soft to the touch yet strong while in use. Absorbency and softness are  
inversely related to strength, often making it difficult to obtain the right balance of  
10 attributes. Accordingly, significant research and development efforts are routinely  
expended to enhance the quality of these products while continuing to reduce cost by,  
for example, improving the production of these products. Although numerous schemes  
have been developed and patented, the search by R&D departments continues to seek  
out new and innovative methods for improving these products.

15 There are numerous methods described in the patent literature for improving the  
quality of packaged paper products. One of the earliest known methods to enhance the  
quality of consumer paper products is described in U. S. Patent No. 3,301,746 by  
Sanford and Sisson, assigned to Procter and Gamble Corporation, and incorporated  
herein by reference in its entirety. This patent describes a papermaking scheme for  
20 enhancing product quality by avoiding overall web compression and by using a pattern  
array of densified regions in the xy plane of the sheet to enhance product strength.

Other early methods for improving the quality of packaged paper products are  
described in U.S. Patent No. 3,812,000 by Salvucci and Yiannos and U.S. Patent No.  
3,821,068 by Shaw. These patents are assigned to Scott Paper Company, each of  
25 which is incorporated herein by reference in its entirety. Shaw discloses a papermaking  
scheme for producing soft tissue by avoiding mechanical compression until the sheet

5 has been dried to at least 80% solids. Salvucci and Yiannos disclose a technique for producing a soft tissue structure by avoiding mechanical compression of an elastomeric containing fiber furnish until the consistency of the web is at least 80% solids.

10 Thicker more absorbent structures can be made using a low batting papermaking felt as described in U.S. Patent No. 4,533,457 by Curran et al., assigned to Scott Paper Company, and incorporated herein by reference in its entirety. U.S. Patent Nos. 5,591,305 and 5,569,358 by Cameron, assigned to James River Corporation, and incorporated herein by reference in their entirety, disclose a low-batting, high-bulk-generating felt with improved dewatering capabilities.

15 A more recent method for improving the quality of a through-air-dried sheet is described in U.S. Patent No. 4,440,597 by Wells and Hensler, assigned to Procter and Gamble Company, and incorporated herein by reference in its entirety. This patent describes a method for increasing the stretch of a paper web by operating the forming section of a paper machine faster than the through air dryer section of the paper machine. As a result of the speed differential, the paper web is inundated into the through air-dryer-fabric leading to enhanced stretch and absorbency properties in the base sheet and resulting product.

20 Fibers and chemicals can be used to enhance the quality of packaged paper products. For example, U.S. Patent No. 5,320,710 by Reeves et al., assigned to Fort James Corporation, and incorporated herein by reference in its entirety, describes a new furnish combination extracted from the species Funifera of the genus Hesperaloe in the Agavaceae family. This furnish has fibers which are very long and which have

5 very fine-geometrical attributes known to enhance tissue and towel performance. U.S. Patent No. 3,755,220 by Freimark and Schaflein, assigned to Scott Paper Company, and incorporated herein by reference in its entirety, describes a debonding scheme for maintaining wet strength while reducing product dry strength-a method known to enhance the handfeel of towel products.

10 The use of bulking fibers can improve the quality of the final end product. U.S. Patent No. 3,434,918 by Bernardin, U.S. Patent No. 4,204,504 by Lesas et al., U.S. Patent No. 4,431,481 by Drach et al., U.S. Patent No. 3,819,470 by Shaw et al., and U.S. Patent No. 5,087,324 by Awofeso et al. disclose the use of bulking fibers in papermaking webs to improve product attributes like thickness, absorbency, and softness. These aforementioned patents are incorporated herein by reference in their entirety.

15 U.S. Patent No. 5,348,620 by Hermans et al., assigned to Kimberly-Clark Worldwide Inc., and incorporated herein by reference discusses a high consistency/high temperature fiber-treatment-process using a disperser to improve product attributes. To improve tissue softness, several approaches are available to the papermaker such as using certain species of hardwood like eucalyptus in stratified webs as disclosed in U.S. Patent No. 4,300,981 by Carstens and U.S. Patent No. 3,994,771 by Morgan et al. The last two patents are incorporated herein by reference in their entirety. These aforementioned patents describe just a few of the many methods developed over the last thirty years to enhance the quality of packaged paper products.

20

There are also numerous schemes for enhancing the productivity of paper

5 machines. For example, gap formers have been developed to enhance sheet drainage ultimately leading to increased machine speed. New developments in Yankee hood design and Yankee cylinder design have allowed improvements in heat transfer coefficients and mass transfer coefficients, ultimately leading to enhanced machine speeds. New developments in forming fabrics, e.g., multi-layer and triple-layer forming  
10 fabrics, have resulted in improved drainage, better fabric life, and enhanced fiber support. These factors translate into enhanced machine speed and productivity. Improvements in press felts, e.g. Scapa's SPECTRA™ felt concept of using a soft polyurethane sandwich near the base of the felt or the use of stratified batting, have led to improvements in felt life, reductions in break-in time, and improvements in water removal at wet presses. These improved press-felt developments have ultimately translated into improved machine speed and productivity. Improvements in Yankee creping adhesives have been helpful to enhance blade wear and reduce sheet plugging. Continuous creping doctors have alleviated the need to frequently change doctor blades. The last two aforementioned developments have led to improvements in  
15 machine speed, reductions in down time, and reductions in paper waste. In spite of all these advances, methods are sought to enhance productivity.

20 The present invention improves the efficiency of known water removal methods by adding one or more pressing units to the production paper machine, in place of or in conjunction with a suction pressure roll. "Pressing units" according to the present invention include those units that physically engage a belt or pressing blanket, which contacts the impression fabric or felt upon which the web travels. "Foraminous endless

5 fabric" as defined in accordance with the present invention includes either an  
impression fabric or felt. "Pressing unit" as defined in accordance with the present  
invention includes any press members allowing deformation of the pressing  
blanket/impression fabric and/or felt/web sandwich to result in asymmetric pressure  
profiles. These pressing units including pressing blankets are generally discussed in the  
10 literature as "shoe presses." Pressing units according to the present invention do not  
include suction pressure rolls since they lead to symmetrical pressure distributions  
frequently mathematically described by sine or haversine functions.

Shoe presses have been used to increase water removal at wet presses,  
ultimately leading to increased machine speed for linerboard grades and more recently,  
newsprint and fine paper grades. The idea of extending the time in a press nip as a  
means to enhance water removal is not a new idea. Nissan in 1954 published a paper  
in Tappi, Vol. 37, No.12, p.597 (1954) suggesting that the use of extended time in a  
press nip would enhance the water removal performance of a press. Over twenty-five  
years, ago Busker published an early paper in Tappi, Vol. 54, No.3, p.373 (1971) on the  
use of extended nip times, as a means to enhance water removal. Beloit Corporation  
commercialized the first open belt wide shoe press on a linerboard machine in 1980 as  
described in an article by J. Blackledge presented during the 2<sup>nd</sup> International Pira  
Conference, entitled 'Modern Technologies in Pressing and Drying', Nov 6-8, 1990, p.  
1. The aforementioned three articles are herein incorporated by reference in their  
entirety.

Figure 1 shows a typical closed belt wide shoe press (see Figure 2 in an article

entitled "New Pressing Technologies for Multiply Board" by J. Breiten in 81<sup>st</sup> Annual Meeting, Technical Section, CPPA, p. A137 for a more detailed drawing). A wide shoe press as described in the literature is essentially a controlled crown roll with a flexible shell and a concave shoe hydrodynamically loaded against each other. The belt or blanket is usually a fabric reinforced polyurethane-coated structure that can be grooved or blind drilled for more efficient water removal. The inside of the belt is generally lubricated with oil, which develops a hydrodynamic film as it passes over the shoe and reduces wear/friction in both surfaces. Wide shoe press nips are on average 5 to 10 times longer than conventional roll press nips (generally, 5" - 10" versus 1" - 2"). Water deflectors (not shown) on the outside surface will dewater the blanket. By utilizing such a wide nip, loads up to 10,000 pli are possible without the risk of damaging blankets and felts or crushing the sheet. The exit side of the shoe features a sharply curved nose designed to pull the sheet directly out of the nip and away from the felt, thus reducing rewet and improving sheet dryness. U.S. Patent No. 4,931,142 describes certain advantages to this type of take off angle in conjunction with long press nips. Rolls do not normally support the belt loop of the wide shoe press. The loop generally is closed off with special head assemblies for containing the oil.

Numerous schemes for improving the operation of shoe presses have been developed over the years. For example, in U.S. Patent No. 5,043,046 by Laapotti and assigned to Valmet Corporation, U.S. Patent No. 4,625,376 by Schiel et al. and assigned to Voith Corporation, and U.S. Patent No. 4,673,461 by Roerig and assigned to Beloit Corporation, methods are described to enclose the shoe press in order to



5 contain the oil within the unit. The previous three patents are incorporated herein by reference. U.S. Patent No. 5,167,768 by Cronin and Roerig and assigned to Beloit Corporation and U.S. Patent No. 5,582,689 by Rolf Van Haag and Hans-Rolf Conard and assigned to Voith Corporation describe methods for varying the pressure distribution in a shoe press. This capability avoids the need to offset the center of  
10 loading or reshape the shoe to change the pressure distribution. These last two patents are also incorporated herein by reference. U.S. Patent No. 5,693,186 by Vallius, assigned to Valmet Corporation, and incorporated herein by reference describes a tension link scheme for containing the loading within the framing of the shoe press apparatus. This scheme ultimately avoids the need to fortify flooring when  
15 operating at high line loads. These are just a few of the many developments that have led to improved operating shoe presses.

In the art of pressing linerboard, newsprint, and fine paper webs with a shoe press, a long shoe with a gradual pressure rise is desirable for good dewatering and enhanced bulk properties. This is especially true for flow controlled webs. Linerboard and to a certain extent newsprint and fine paper have flow controlled pressing  
20 conditions. Flow controlled pressing conditions occur when the time in the nip becomes an important factor determining the amount of water removed from the web. High pressure can be attained with these long shoes but it requires high line loads. Figure 2 shows the relationship between peak pressure (i.e., the maximum pressure in the nip) and line load (i.e., the total force divided by linear width) for shoe press nips compiled from an extensive but not exhaustive search of the literature. Table I describes the

5 literature references used to develop Figure 2.

Table I: References Used to Generate Figure 2.

Reference Number	Source
1	U.S. Patent No. 5,167,768
2	W. Schuwerk, Paper Age, September, 1997, p.18.
3	N. Anderson, Journal of Tappik, Vol. 21, No. 1, 1998, p.52.
4	J. Kinnunen and A. Kiviranta, Paperi Ja Puu-Paper and Timber Vol. 74, No. 4, 1992, p. 314.
5	J. Kivimaa, M. Laurikainen, and K. Pansu, PITA Water Removal Conference 1997 York, Paper Technology, April, 1998.
6	J. Blackledge and D. Lange, 2 <sup>nd</sup> International Pira Conference, "Modern Technologies in Pressing and Drying", Nov. 6-8, 1990, p.1.
7	M. Radtke, 79 <sup>th</sup> Annual Meeting, Technical Section, CPPA, p. A221.
8	J. Breiten, 81 <sup>st</sup> Annual Meeting, Technical Section, CPPA, p. A137.
9	E. Tenfalt, J. Wilmenius, and O. Swanberg, Nordic Pulp and Paper Research Journal, 1998, p.16.
10	D. Lange and M. Radtke, Papermaker, July 1996, p. 16.
11	"Chemical Systems Boost Dry Content", PPI, February, 1989, p. 41.

The graph in Figure 2 shows that shoe presses normally operate at high line load conditions, usually greater than 270kN/m and at high peak pressures. It also shows that shoe presses are not operated at low line loads and at high peak pressures (e.g., see the crosshatched region in Figure 2).

In the art of making tissue by the conventional wet pressing operation, Yankee dryers are loaded with suction pressure rolls to remove water from the tissue web and attach the web to the dryer for further processing by the creping operation. The

5 pressure distribution in the suction pressure roll nip is symmetrical in shape and is described mathematically by a sine or a haversine curve. Suction pressure rolls loaded to a Yankee dryer are routinely run at line loads less than 100 kN/m and at peak pressures of less than 4500 kN/m<sup>2</sup>. In the lower left-hand corner of Figure 2 some typical peak pressure versus line load data for suction pressure rolls are shown. The  
10 deflection of large, conventional Yankee dryers due to hoop stress levels limits the line load to less than about 100 kN/m. As a result, it is very difficult to attain high peak pressures in the nip at these low line loads, since the pressure distribution cannot be altered. This limitation has extreme consequences for tissue grades since they are pressure controlled, i.e., the flow resistance in the web is low due to the use of high  
15 freeness furnishes and low basis weight webs, thus it is believed that peak pressure, not time in the nip, controls press dewatering. These suction pressure rolls suffer from other disadvantages. For example, since the nip diverges after the maximum pressure is achieved, rewet can occur for a large part of the press nip. A typical suction pressure roll curve appears in Figure 3, where nip divergence is apparent. Also, the suction  
20 pressure roll unit is not flexible so that the line load needs to be fixed and matched to a given Yankee crown condition in order to obtain a uniform nip profile across the machine. Furthermore, since the loading cylinders are located at each end of the pressure roll, profiling capabilities are very limited.

The use of conventional shoe presses on a Yankee dryer at the maximum hoop  
25 stress limit of 100kN/m would lead to very low peak pressures as Figures 2 and 3 demonstrate. For example, with a 120 mm shoe at 100 kN/m, the typical peak pressure

5 is on the order of 1700 kN/m as Figure 3 demonstrates. Since the press nip for low weight tissue and towel grades is pressure controlled, the very low peak pressure could cause a decrease in post press dryness, ultimately causing a loss in production. The counter roll in a conventional shoe press is small by comparison to the diameter of a Yankee dryer. As a result, the use of a conventional shoe shape would make it very  
10 difficult to remove the felt/fabric from the sheet at the nip exit. Therefore, conventional shoe shapes and conventional felt/fabric takeoff angles would exacerbate rewet for low weight absorbent products.

Currently, there are no commercial uses of shoe press technology in the production of absorbent paper products. U.S. Patent No. 5,795,440 by Ampulski et al., and U.S. Patent No. 5,776,307 by Ampulski et al.-both assigned to Procter and Gamble Corporation and both incorporated herein by reference, describe a scheme for making a shaped web by pressing an embryonic web into an imprinting fabric between two  
15 felts. These patents use a shoe press assembly in the preparation of a wet pressed paper web. Ampulski et al., like others using pressing units, teaches the use of longer conventional press nips. Ampulski et al. discloses that the nip length is greater than 3.0  
20 inches and may be as long as 20.0 inches. Ampulski et al. achieves this extended nip length through the use of a shoe press. Ampulski et al., like all previous users of shoe presses, fails to consider the use of increased peak pressure.

5

International patent application WO 97/43483 by Hermans and Friedbauer, assigned to Kimberly-Clark Worldwide, Inc., and incorporated herein by reference discloses that extended nip presses, while having been successfully used for making paperboard, have not been used to make low density paper products such as tissue because the high pressure and longer dwell times in an extended nip press serve to densify the sheet beyond that experienced by conventional tissue wet pressing methods. Hermans and Friedbauer overcome the increased density due to extended nip pressing by incorporating modified resilient fibers (e.g., chemically cross-linked cellulosic fibers) in the web and by wet micro-shaping the web. They also disclose shoe lengths typically in the range of 5 to 10 inches. Like Ampulski et al., Hermans and Friedbauer do not consider critical peak pressures or line loads as important.

10

15

20

U.S. Patent No. 5,393,384 by Steiner et al., and assigned to J.M. Voith, GmbH

(hereinafter "the '384 patent") generally describes the use of a shoe press in the production of a tissue web. The '384 patent describes the use of a shoe press preceding or contacting a Yankee drying cylinder. The shoe press is used in conjunction with an impermeable belt to reduce remoistening of the sheet by the felt. These authors used the impermeable belt since they state: "the prevailing opinion in selecting suitable drying presses in contingency on the web thickness so far has been that for drying thin webs there are only simple roll presses suited which generate a sufficiently high contact pressure for a short time, thus optimally removing the water from a thin web (tissue web) due to the short path, whereas shoe type presses are suited essentially for drying thick, heavy webs, since they generate a persistent

25

5 pressure which allows the water sufficient time for the considerable longer path in leaving the web." Critical peak pressure and line loads are not discussed in the disclosure. Since the shoe press described in this disclosure is conventional, a pressure curve for this type of shoe press is most likely similar to the "typical shoe press curve" illustrated in Figure 3.

10 Voith, the assignee of the '384 patent, continues to develop the use of a shoe press for the production of paper products. U.S. Patent No. 5,500,092 by Schiel describes a tissue making machine using a triple press nip where the second nip is a shoe press nip. The criticality of pressure distribution shape and peak pressure/line load magnitudes are not disclosed in the '092 patent. In the September 1997 article W. Schuwerk, "Shoe Presses and Sleeves for Newsprint-Concepts and Initial Operating Experience," PaperAge, Pp. 18-23, Voith described the advantages of their NIPCOFLEX shoe press. According to that article, "[T]o obtain optimum product characteristics, dewatering in the press must [therefore] show as flat a pressure gradient as possible." In fact, the shoe press described in the article refers to the third  
15 section of a newsprint paper machine operating at a line loading of 850 kN/m and a peak pressure of ~5.6 MPa, typical of standard conventional shoe designs and well outside the range of the present invention.

20 U.S. Patent No. 4,931,142 by Steiner, Muller, Schiel, and Flamig, assigned to Voith Corporation and incorporated herein by reference in its entirety describes a method of eccentrically arranging a press blanket with respect to the press plane. This  
25 arrangement enables the blanket upon leaving the press nip to immediately move

5 steeply downward and away from the sheet in order to reduce remoistening of the web. Methods of varying the felt angle with respect to the traveling web in a double felted press nip were disclosed to avoid remoistening the sheet and for quick release of the sheet from the felt. Steiner et al. also discloses that the joint path of travel of the paper web, felt, and blanket can be made substantially shorter than prior art. By utilizing the Steiner et al. invention, the joint travel of the felt, web, and blanket can be made equal to zero, i.e., the web can detach itself from the felt directly at the emergence from the press nip. Steiner et al. does not address low line loads and high peak pressures needed for optimum shoe press performance on Yankee dryers. It also does not disclose the need to taper the press shoe to achieve minimized rewet.

15 U.S. Patent No. 5,556,511 by Bluhm and Gotz, assigned to Sulzer-Escher Wyss, and incorporated herein by reference describes a process for making toilet tissue webs whereby a web is wet pressed in a heated pressing arrangement. The heated pressing arrangement can be a shoe press. This disclosure does not address the importance of proper choice of peak pressure, line load, and shoe shape for making absorbent products at high speeds. In fact, the critically of line loads and peak pressures is not discussed. Bluhm and Gotz like all previous users of shoe presses, fails to consider the use of increased peak pressure at low line loads as a means to improve water removal.

20 U.S. Patent No. 4,973,384 by Crouse, Pulkowski, and Porter, assigned to Beloit Corporation, and incorporated herein by reference describes a process for using a heated extended nip press for optimizing sheet properties without lamination. To accomplish the aforementioned task Crouse et al. found that by application of pressure

5 for an increased period of time, the increased residence time enables the removal of more water from the formed web. As a result, these authors teach toward the use of a conventional long shoe design. They also found that for a heated extended nip press by "gradually decreasing pressure in machine direction toward the trailing edge of the shoe, rapid flashing of steam from the emerging pressed web was avoided." As a  
10 result these authors teach away from the use of a heavy peaked pressure distribution at the exit side of a shoe press nip.

WO 97/16593 by Wedel and Worcester incorporated herein by reference discloses an impulse drying method for tissue structures using a shoe press and an induction heater. This disclosed impulse-drying method is intended to replace the  
15 Yankee dryer with its associated problems. These authors list the issues with Yankee dryers as being limited in surface temperature to 185°F, as being limited in line load to 500 pli due to shell thickness limitations, and as being limited in roll diameter. These authors state that shoe length is typically ten inches for the impulse drying unit. The line loads disclosed are 1000 pli to 10,000 pli. As a result, this application teaches away  
20 from the combined use of a low line load with a substantial peak pressure.

Contrary to the current state of the art, the present inventors have, quite unexpectedly, found that in the production of absorbent paper products, the use of a steep, sharp pressure gradient and controlled separation when producing absorbent paper can improve dewatering efficiency without adversely affecting product properties.  
25 An example of the pressure profile of the new shoe design for absorbent paper production according to the present invention is illustrated in Figure 3.



5                   The present inventors unexpectedly discovered that good sheet dewatering and appropriate bulk/strength properties for low weight absorbent products could be attained with this pressure optimized shoe press. The optimized pressure conditions can be achieved according to the present invention by shaping the shoe, tilting the shoe in the shoe press, reducing the length of the shoe in the shoe press, and/or tapering the exit side of the shoe. In addition, these conditions can also be achieved by deflecting the pressing blanket from the web carrying foraminous-endless-fabric at a point nearly simultaneous with separation of the foraminous-endless-fabric from the nascent web, thereby reducing rewet. These techniques enable the pressure optimized shoe press according to the present invention to achieve improved dewatering while maintaining bulk with line loads less than about 240kN/m and peak pressures greater than about 2000 kN/m<sup>2</sup>.

#### SUMMARY OF THE INVENTION

Further advantages of the invention will be set forth in part in the description, which follows and in part will be apparent from the description. The advantages of the invention may be realized and attained by means of the instrumentalities and combinations particularly pointed out in the appended claims.

To achieve the foregoing advantages and in accordance with the purpose of the invention, as embodied and broadly described herein, there is disclosed:

An apparatus for forming an absorbent paper sheet product comprising:  
a moving foraminous endless fabric;

5

means for depositing a nascent web for the absorbent paper sheet on the foraminous endless fabric;

a moving endless pressing blanket;

a Yankee drying cylinder; and

a pressing unit engaging the pressing blanket adapted to urge the nascent web

10

for the absorbent paper sheet on the foraminous endless fabric into engagement with the Yankee drying cylinder thereby forming a nip, the pressing unit being configured to create a peak engagement pressure of at least about 2000 kN/m<sup>2</sup> at an overall line load of less than about 240 kN/m.

There is further disclosed:

15

An apparatus for forming an absorbent paper sheet product comprising:

a moving foraminous endless fabric;

means for depositing a nascent web for the absorbent paper sheet on the foraminous endless fabric;

a moving endless pressing blanket;

20

a Yankee drying cylinder; and

a pressing unit engaging the pressing blanket adapted to urge the nascent web

for the absorbent paper sheet on the foraminous endless fabric into engagement with the Yankee drying cylinder thereby forming a nip, the pressing unit being configured to create a peak engagement pressure of at least about 2000 kN/m<sup>2</sup> at an overall line load of less than about 240 kN/m,

25

5 the pressing unit being configured to disengage the web from the foraminous endless fabric such that rewet of the nascent web by the foraminous endless fabric is less than about 50% of the rewet predicted by the Sweet equations based upon the properties of the foraminous endless fabric and the nascent web.

There is still further disclosed:

10 An apparatus for forming an absorbent paper sheet product comprising:  
a moving foraminous endless fabric;

means for depositing a nascent web for the absorbent paper sheet on the foraminous endless fabric;

a moving endless pressing blanket;

15 a Yankee drying cylinder; and

a pressing unit engaging the pressing blanket adapted to urge the nascent web for the absorbent paper sheet on the foraminous endless fabric into engagement with the Yankee drying cylinder thereby forming a nip, the pressing unit being configured to create a peak engagement pressure of at least about 2000 kN/m<sup>2</sup> at an overall line load of less than about 240 kN/m,

20 the pressing unit being configured to both disengage the web from the foraminous endless fabric and disengage the foraminous endless fabric from the pressing blanket at a nip length of less than about one inch from the point the nip pressure reaches zero.

25 There is still further disclosed:

An apparatus for forming an absorbent paper sheet product comprising:

5 a moving foraminous endless fabric;

means for depositing a nascent web for the absorbent paper sheet on the foraminous endless fabric;

a moving endless pressing blanket;

a transfer cylinder; and

10 a pressing unit engaging the pressing blanket adapted to urge the nascent web for the absorbent paper sheet on the foraminous endless fabric into engagement with the transfer cylinder thereby forming a nip, the pressing unit being configured to create a peak engagement pressure of at least about 2000 kN/m<sup>2</sup> at an overall line load of less than about 240 kN/m.

15 There is still further disclosed:

An apparatus for forming an absorbent paper sheet product comprising:

a moving foraminous endless fabric;

means for depositing a nascent web for the absorbent paper sheet on the foraminous endless fabric;

20 a moving endless pressing blanket;

a transfer cylinder; and

a pressing unit engaging the pressing blanket adapted to urge the nascent web for the absorbent paper sheet on the foraminous endless fabric into engagement with the transfer cylinder thereby forming a nip, the pressing unit being configured to create  
25 a peak engagement pressure of at least about 2000 kN/m<sup>2</sup>.

There is still further disclosed:

5

An apparatus for forming an absorbent paper sheet product comprising:

a moving foraminous endless fabric;

means for depositing a nascent web for the absorbent paper sheet on the

foraminous endless fabric;

a moving endless pressing blanket;

10

a backing roll; and

a pressing unit engaging the pressing blanket adapted to urge the nascent web

for the absorbent paper sheet on the foraminous endless fabric into engagement with

the backing roll thereby forming a nip, the pressing unit being configured to create a

peak engagement pressure of at least about 2000 kN/m<sup>2</sup> at an overall line load of less

than about 240 kN/m.

There is still further disclosed:

A method of making an absorbent paper sheet product comprising:

depositing a nascent web for the absorbent paper sheet product on a moving

foraminous endless fabric; and

contacting the moving foraminous endless fabric bearing the deposited nascent

web with a moving endless pressing blanket engaged with a pressing unit thereby

forming a nip, the pressing unit being configured to create a peak engagement pressure

of at least about 2000 kN/m<sup>2</sup> at an overall line load of less than about 240 kN/m.

There is also disclosed:

25

A method of making an absorbent paper sheet product comprising:

depositing a nascent web for the absorbent paper sheet product on a moving

5 foraminous endless fabric;

contacting the moving foraminous endless fabric bearing the deposited nascent web with a moving endless pressing blanket engaged with a pressing unit thereby forming a nip, the pressing unit being configured to create a peak engagement pressure of at least about 2000 kN/m<sup>2</sup> at an overall line load of less than about 240 kN/m;

10 transferring the web to a Yankee drying cylinder; and  
creping the web from the Yankee drying cylinder.

There is finally disclosed:

A method of making an absorbent paper sheet product comprising:

15 depositing a nascent web for the absorbent paper sheet product on a moving foraminous endless fabric;

contacting the moving foraminous endless fabric bearing the deposited nascent web with a shoe press thereby forming a nip between the shoe press and a Yankee drying cylinder, the shoe press being configured to create a peak engagement pressure of at least about 2000 kN/m<sup>2</sup> at an overall line load of less than about 240 kN/m;

20 disengaging the web from the foraminous endless fabric in the nip onto a Yankee drying cylinder;

drying the web on the Yankee drying cylinder; and  
creping the web from the Yankee drying cylinder.

The accompanying drawings are included to provide a further understanding of  
25 the invention and are incorporated in and constitute a part of the specification. The drawings illustrate embodiments of the invention and, together with the description,

5 serve to explain the principles of the invention.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates a side view of a typical stand alone shoe press.

10 Figure 2 illustrates the relationship between peak pressure and line load for a variety of shoe press arrangements found in the literature, as well as for Yankee suction pressure rolls.

Figure 3 illustrates nip pressure profiles for a suction pressure roll, a typical shoe press, and a shoe press made according to the present invention.

Figure 4 illustrates one conventional wet press processing apparatus.

15 Figure 5 illustrates one conventional through-air-drying processing apparatus.

Figure 6 illustrates a typical pressure profile in the nip of a suction pressure roll, backing roll, or transfer cylinder according to the prior art.

Figure 7 illustrates a pressure profile in the nip of a shoe press.

20 Figure 8 illustrates a preferred pressure profile in the nip of a shoe press where the negative pressure corresponds to the vacuum level in the felt.

Figure 9 illustrates a shoe press with a large diameter transfer cylinder where the felt rides the web causing rewet after the press nip.

25 Figure 10 illustrates a tapered shoe in a shoe press with a large diameter transfer cylinder where the felt is rapidly separated from the web but not from the pressing blanket.

5                    Figure 11 illustrates a tapered shoe in a shoe press with a large diameter transfer cylinder where the felt is simultaneously stripped from the sheet and from the pressing blanket on the exit side of the nip.

10                    Figure 12 shows a plot of cold Yankee press solids versus line loading for a conventional 120 mm shoe, for a 50 mm shoe made according to the present invention, and for a suction pressure roll.

                    Figure 13 illustrates a side view of a typical stand alone shoe press with a blanket having void space.

                    Figure 14 illustrates a blind drilled blanket or belt.

                    Figure 15 illustrates a grooved blanket or belt.

#### DETAILED DESCRIPTION

15                    In the production of absorbent paper products, paper web drying efficiency and paper web moisture removal directly affect machine speed, and therefore have a significant effect on the productivity that can be attained on a papermachine. The present invention improves paper web moisture removal through the controlled use of a pressing unit in conjunction with a backing roll and/or a transfer cylinder or Yankee drying cylinder. An absorbent paper web as defined herein includes bath tissue, paper towels, paper napkins, wipers, and facial tissue. The basis weight of such products and their base sheets are in the range of about 8 lb/3000ft<sup>2</sup> to about 50 lb/3000ft<sup>2</sup>.

20                    According to the present invention, absorbent paper may be produced using any known method or papermaking scheme. The most common papermaking methods are



(I) conventional wet pressing (CWP) and (II) through-air-drying (TAD). In a conventional wet press process, i.e., apparatus (10), as exemplified in Figure 4, a furnish is fed by means not shown through conduits (40, 41) to headbox chambers (20, 20'). A web (W) is formed on a conventional wire former on fabric (12), supported by rolls (18, 19), from a liquid slurry of pulp, water and other chemicals. Materials removed from the web through fabric (12) in the forming zone are returned to silo (50), from saveall (22) through conduit (24). The web is then transferred to a moving felt (14), supported by roll (11) for pressing and drying. Materials removed from the web during pressing or from the Uhle box (29) are collected in saveall (44) and fed to white water conduit (45). The web is pressed by suction pressure roll (16) against the surface of a rotating Yankee dryer cylinder (26), which is heated to cause the paper to substantially dry on the cylinder surface. The moisture within the web as it is laid on the Yankee surface causes the web to transfer to the surface. Liquid adhesive may be applied to the surface of the dryer to provide substantial adherence of the web to the creping surface. The web is then creped from the surface with a creping blade (27). The creped web is then usually passed between calender rollers (not shown) and rolled up on reel (28) prior to further converting operations, for example, embossing.

A web may alternatively be subjected to vacuum deformation on an impression fabric, alone or in conjunction with other physical deformation processes, and a dewatering step which removes water from the web to a solids content of at least about 30% without the need for overall physical compression. This type of process is conventionally referred to as a through-air-drying process or TAD process. This

5 process is generally described in U.S. Patent Nos. 3,301,746 to Sanford et al. and 3,905,863 to Ayers, which are incorporated herein by reference in their entirety.

10 As an example, one conventional TAD process is illustrated in Figure 5. In this process, fibers are fed from a headbox (10) to a converging set of forming wires (20,30). In this twin wire forming arrangement water is removed from the web by centrifugal forces and by vacuum means. The wet nascent web is cleanly transferred to forming wire (30) via Uhle box (40). The web can be optionally processed to remove water by vacuum box (50) and steam shroud (60). The web is carried along forming fabric (30) until it is transferred to a TAD fabric (70) at junction (80) by means of a vacuum pickup shoe (90). The web is further dewatered at dewatering box (100) to increase web solids. Besides removing water from the web, vacuum pickup shoe (90) and dewatering box (100) inundate the web into TAD fabric (70) causing bulk and absorbency improvements.

20 Further enhancements in bulk and absorbency can be obtained by operating the speed of the forming section (i.e., the speeds of forming fabrics 20 and 30) faster than the speed of TAD fabric (70). This is referred to as fabric/fabric creping. In this manner the web is inundated and wet shaped into the fabric creating bulk and absorbency. Thickness created by wet shaping is more effective in generating absorbency (i.e. less structural collapse) than thickness created in the dry state, e.g., by conventional embossing. The web is then carried on TAD fabric (70) to drying unit (110) where heated air is passed through both the web and the fabric to increase the solids content of the web. Generally, the web is 30 to 95% dry after exiting drying unit (110). In one

5 process, the web may be removed directly from TAD fabric (70) in an uncreped state. In the embodiment shown in Figure 5, the web is transferred from TAD fabric (70) to Yankee dryer cylinder (130) and is creped from dryer cylinder (130) via creping blade (150). The creped web is then usually passed between calender rollers (160) and rolled up on reel (170) prior to further converting operations, for example, embossing to make roll products.

10 According to the present invention, an absorbent paper web can be made by dispersing fibers into aqueous slurry and depositing the aqueous slurry onto the forming wire of a paper making machine. Any art recognized forming scheme might be used. For example, an extensive but non-exhaustive list includes a crescent former, a C-wrap twin wire former, an S-wrap twin wire former, a suction breast roll former, a fourdrinier former, or any art recognized forming configuration. The particular forming apparatus is not critical to the success of the present invention. The forming fabric can be any art recognized foraminous member including single layer fabrics, double layer fabrics, triple layer fabrics, photopolymer fabrics, and the like. Non-exhaustive background art in the forming fabric area include U.S. Patent Nos. 4,157,276; 4,605,585; 4,161,195; 3,545,705; 3,549,742; 3,858,623; 4,041,989; 4,071,050; 4,112,982; 4,149,571; 4,182,381; 4,184,519; 4,314,589; 4,359,069; 4,376,455; 4,379,735; 4,453,573; 4,564,052; 4,592,395; 4,611,639; 4,640,741; 4,709,732; 4,759,391; 4,759,976; 4,942,077; 4,967,085; 4,998,568; 5,016,678; 5,054,525; 5,066,532; 5,098,519; 5,103,874; 5,114,777; 5,167,261; 5,199,467; 5,211,815; 5,219,004; 5,245,025; 5,277,761; 5,328,565; and 5,379,808 all of which are incorporated herein by reference

5 in their entirety. The particular forming fabric is not critical to the success of the present invention. One forming fabric found particularly useful with the present invention is Appleton Mills Forming Fabric 2184 made by Appleton Mills Forming Fabric Corporation, Florence, MS.

10 Papermaking fibers used to form the absorbent products of the present invention include cellulosic fibers commonly referred to as wood pulp fibers, liberated in the pulping process from softwood (gymnosperms or coniferous trees) and hardwoods (angiosperms or deciduous trees). Cellulosic fibers from diverse material origins may be used to form the web of the present invention. These fibers include non-woody fibers liberated from sugar cane, bagasse, sabai grass, rice straw, banana leaves, 15 paper mulberry (i.e., bast fiber), abaca leaves, pineapple leaves, esparto grass leaves, and fibers from the genus Hesperaloe in the family Agavaceae. Also recycled fibers which may contain any of the above fiber sources in different percentages, can be used in the present invention. Suitable fibers are disclosed in U.S. Patent Nos., 5,320,710 and 3,620,911, both of which are incorporated herein by reference.

20 Papermaking fibers can be liberated from their source material by any one of the number of chemical pulping processes familiar to one experienced in the art including sulfate, sulfite, polysulfide, soda pulping, etc. The pulp can be bleached if desired by chemical means including the use of chlorine, chlorine dioxide, oxygen, etc. Furthermore, papermaking fibers can be liberated from source material by any one of a 25 number of mechanical/chemical pulping processes familiar to anyone experienced in the art including mechanical pulping, thermomechanical pulping, and chemi-

5 thermomechanical pulping. These mechanical pulps can be bleached, if necessary, by a number of familiar bleaching schemes including alkaline peroxide and ozone bleaching.

10 The suspension of fibers or furnish may contain chemical additives to alter the physical properties of the paper produced. These chemistries are well understood by the skilled artisan and may be used in any known combination.

15 The pulp can be mixed with strength adjusting agents such as wet strength agents, dry strength agents and debonders/softeners. Suitable wet strength agents will be readily apparent to the skilled artisan. A comprehensive but non-exhaustive list of useful wet strength aids include urea-formaldehyde resins, melamine formaldehyde resins, glyoxylated polyacrylamide resins, polyamide-epichlorhydrin resins and the like. Thermosetting polyacrylamides are produced by reacting acrylamide with diallyl dimethyl ammonium chloride (DADMAC) to produce a cationic polyacrylamide copolymer which is ultimately reacted with glyoxal to produce a cationic cross-linking wet strength resin, glyoxylated polyacrylamide. These materials are generally described in U.S. Patent Nos. 3,556,932 to Coscia et al. and 3,556,933 to Williams et al., both of which are incorporated herein by reference in their entirety. Resins of this type are commercially available under the tradename of PAREZ 631NC by Cytec Industries. Different mole ratios of acrylamide/DADMAC/glyoxal can be used to produce cross-linking resins, which are useful as wet strength agents. Furthermore, 20 other dialdehydes can be substituted for glyoxal to produce thermosetting wet strength characteristics. Of particular utility are the polyamide-epichlorhydrin resins, an example

5 of which is sold under the tradenames Kymene 557LX and Kymene 557H by Hercules Incorporated of Wilmington, Delaware and CASCAMID® from Borden Chemical Inc. These resins and the process for making the resins are described in U.S. Patent No. 3,700,623 and U.S. Patent No. 3,772,076 each of which is incorporated herein by reference in its entirety. An extensive description of polymeric-epihalohydrin resins is given in Chapter 2: Alkaline -Curing Polymeric Amine-Epichlorohydrin by Espy in *Wet -*  
10 *Strength Resins and Their Application* (L. Chan, Editor, 1994), herein incorporated by reference in its entirety. A reasonably comprehensive list of wet strength resins is described by Westfelt in Cellulose Chemistry and Technology, Volume 13, p. 813, 1979, which is incorporated herein by reference. The pulp, when making towel grades according to the present invention, preferably contains up to about 30 lbs/ton, more  
15 preferably from 10 to 20 lbs/ton of wet strength aids. Wet strength resins are not normally added to tissue grades.

Suitable dry strength agents will be readily apparent to one skilled in the art. A comprehensive but non-exhaustive list of useful dry strength aids includes starch, guar  
20 gum, polyacrylamides, carboxymethyl cellulose and the like. Of particular utility is carboxymethyl cellulose, an example of which is sold under the tradename Hercules CMC by Hercules Incorporated of Wilmington, Delaware. The pulp preferably contains from 0 to 10 lbs/ton, more preferably from 1 to 5 lbs/ton of dry strength aid.

Suitable debonders will be readily apparent to the skilled artisan. Debonders or  
25 softeners may also be incorporated into the pulp or sprayed upon the web after its formation. The pulp preferably contains from 0 to 10 lbs/ton, more preferably from 1 to

5

5 lbs/ton of debonder/softener.

10

The present invention may be used with a particular class of softener materials - amido amine salts derived from partially acid neutralized amines. Such materials are disclosed in U.S. Patent No. 4,720,383. Evans, Chemistry and Industry, 5 July 1969, Pp. 893-903; Egan, J. Am. Oil Chemist's Soc., Vol. 55 (1978), Pp. 118-121; and Trivedi et al., J. Am. Oil Chemist's Soc., June 1981, Pp. 754-756, incorporated by reference in their entirety, indicate that softeners are often available commercially only as complex mixtures rather than as single compounds. While the following discussion will focus on the predominant species, it should be understood that commercially available mixtures would generally be used in practice.

15

20

Quasoft 202-JR is a suitable softener material, which may be derived by alkylating a condensation product of oleic acid and diethylenetriamine. Synthesis conditions using a deficiency of alkylation agent (e.g., diethyl sulfate) and only one alkylating step, followed by pH adjustment to protonate the non-ethylated species, result in a mixture consisting of cationic ethylated and cationic non-ethylated species. A minor proportion (e.g., about 10%) of the resulting amido amine cyclize to imidazoline compounds. Since only the imidazoline portions of these material are quaternary ammonium compounds, the compositions as a whole are pH-sensitive. Therefore, in the practice of the present invention with this class of chemicals, the pH in the headbox should be approximately 6 to 8, more preferably 6 to 7 and most preferably 6.5 to 7.

25

Quaternary ammonium compounds, such as dialkyl dimethyl quaternary ammonium salts are also suitable particularly when the alkyl groups contain from about

14 to 20 carbon atoms. These compounds have the advantage of being relatively insensitive to pH.

Biodegradable softeners can be utilized. Representative biodegradable cationic softeners/debonders are disclosed in U.S. Patent Nos. 5,312,522; 5,415,737; 5,262,007; 5,264,082; and 5,223,096, all of which are incorporated herein by reference in their entirety. These compounds are biodegradable diesters of quaternary ammonia compounds, quaternized amine-esters, and biodegradable vegetable oil based esters functional with quaternary ammonium chloride and diester dierucyldimethyl ammonium chloride and are representative biodegradable softeners.

The fibrous web is then either deposited on an impression drying fabric, in the case of the TAD process or on a dewatering felt for the CWP process. Any art recognized fabrics or felts could be used with the present invention. For example, a non-exhaustive list of impression fabrics would include plain weave fabrics described in U.S. Patent No. 3,301,746; semitwill fabrics described in U.S. Patent Nos. 3,974,025 and 3,905,863; bilaterally-staggered-wicker-basket-cavity type fabrics described in U.S. Patent Nos. 4,239,065 and 4,191,609; sculptured/load bearing layer type fabrics described in U.S. Patent No. 5,429,686; photopolymer fabrics described in U.S. Patent Nos. 4,529,480, 4,637,859, 4,514,345, 4,528,339, 5,364,504, 5,334,289, 5,275,799, and 5,260,171; and fabrics containing diagonal pockets described in U.S. Patent No. 5,456,293. The aforementioned patents are incorporated herein by reference, in their entirety. Any art-recognized-felt can be used with the present invention. For example, felts can have double-layer base weaves, triple-layer base weaves, or laminated base



5 weaves. Preferred felts according to the present invention are those having the laminated base weave design. A wet-press-felt found particularly useful with the present invention is AMFlex 3 made by Appleton Mills Corporation. Non-exhaustive background art in the press felt area includes U.S. Patent Nos. 5,657,797; 5,368,696; 4,973,512; 5,023,132; 5,225,269; 5,182,164; 5,372,876; and 5,618,612 all-of-which are  
10 incorporated herein by reference in their entirety. After the web made by the conventional wet press process has reached a solids content of about 15 %, more preferably about 20 %, the web/foraminous fabric sandwich is contacted with a pressing blanket engaged with a pressing unit, one embodiment in the art referred to as a shoe press. In a similar web made by through air drying, the web/foraminous fabric sandwich is preferably contacted with the pressing blanket engaged with a pressing unit after the web has reached a solids content of at least about 20%, more preferably at least about 25%.

The pressing unit including a pressing blanket according to the present invention can have any art-recognized configuration. The nip can be created between the pressing unit and a backing roll, in the case of a stand-alone pressing unit, or can be created between the pressing unit and a transfer cylinder. As used in the present invention, backing roll refers to a roll that contacts the web but does not remove the fibrous web from the carrier fabric or felt. Backing rolls for use according to the present invention may be heated or cold. The backing roll can be made of hard rubber or metal.  
20 When the rolls are heated with an induction heater the roll is preferably constructed or coated with high diffusivity material, such as copper, to aid in increasing heat transfer.

5 As used in the present invention, transfer cylinder refers to a roll that picks up the fibrous web thereby transferring the fibrous web from the foraminous carrier fabric upon which it had been carried. Typical transfer cylinders according to the present invention can include a steel roll, a metal coated roll, a granite roll, a Yankee drying cylinder, and a gas fired drying cylinder. Transfer cylinders for use according to the present method  
10 may be heated or cold. When the transfer cylinder is heated with an induction heater the cylinder is preferably constructed or coated with high diffusivity material, such as copper, to aid in increasing heat transfer. One or more transfer cylinders may be used in the process according to the present invention.

Heat is preferably applied to the transfer cylinder and/or backing roll. Heat can be applied by any art-known scheme including induction heating, oil heating and steam heating. Commercial available induction heaters can generate very high energy-transfer rates. An induction heater induces electrical current to the conducting roll surface. Since the induced current can be quite large, this factor produces a substantial amount of resistive heating in the conducting roll. Backing roll or transfer  
15 cylinder temperature can be anywhere from ambient to 700 ° F but are more preferably from 180 ° F to 500 ° F. Preferred heating schemes according to the present invention are induction heating and steam-heating.

Increased temperature in the backing roll or transfer cylinder decreases the viscosity of the water and makes the sheet more deformable hence improving water  
20 removal. Also, increased temperature and operating pressure bring the sheet into intimate contact with the transfer cylinder or backing roll, which improves heat transfer

5 to the web. Furthermore, high steam pressure in the web within the nip can aid in rapidly displacing water from the sheet to the felt.

The pressing unit including a pressing blanket according to the present invention is preferably a shoe press. A shoe press includes a shoe element(s), which is pressed against the backing roll or transfer cylinder. The shoe element is loaded hydrodynamically against the backing roll or transfer cylinder causing a nip to be formed. A pressing belt or blanket traverses the shoe press nip with the fibrous web in contact with the foraminous fabric.

Pressing blankets can be smooth, or to enhance water removal at the press they can be grooved or blind drilled. Conventional pressing blanket designs contain a fabric coated with polyurethane where the fabric is used as reinforcement. Other pressing blanket designs use yarns embedded in the polyurethane to provide reinforcement. One preferred pressing blanket according to the present invention is a yarn reinforced blanket design under the tradename QualiFlex B, which is supplied by Voith Sulzer Corporation.

The shoe element length can be less than about 7 inches but is more preferably less than about 3 inches for the present invention. According to the present invention the shoe element will also be referred to as a hydraulic engagement member. Shoe designs can be hydrodynamic, hydrodynamic pocket, or hydrostatic. In the hydrodynamic shoe design, the oil lubricant forms a wedge at the ingoing side of the nip ultimately causing the formation of a thin oil film that protects the blanket and the shoe. The hydrodynamic pocket design incorporates a machined full width pocket in the shoe

5 used for emptying the oil in the pressurized zone of the shoe. The final design is the hydrostatic design where oil is fed into the center region of the shoe. The preferred shoe design according to the present invention is hydrodynamic.

Shoe presses for use according to the present invention can be open or closed. Early shoe press designs were the open belt configurations where an impermeable pressing blanket encircled a series of rollers similar to that of a fabric or felt run. These open designs suffered from papermachine system contamination by oil. The oil loss was at one time, up to 20 liters per day on some systems. The open shoe design is also inferior to a closed design since it cannot be operated in the inverted mode. The closed shoe design alleviates the oil contamination issue and is therefore preferred for use in the present invention.

According to one embodiment of the present invention, the peak pressure in the shoe press is preferably greater than about 2000 kN/m<sup>2</sup>, with a line load of preferably less than about 240 kN/m. In another embodiment of the present invention, for conventionally made wide-Yankee-dryers the peak pressure is preferably greater than about 2000 kN/m<sup>2</sup>, while the line load is preferably less than about 175 kN/m and more preferably less than about 100 kN/m. For the purposes of the present invention, kN/m is an abbreviation for kilonewtons per meter and kN/m<sup>2</sup> is an abbreviation for kilonewtons per square meter.

The sheet can be creped from the transfer cylinder by any art-recognized methods using any art recognized creping aid.

The maximum line load a current standard Yankee can sustain is on the order of

100kN/m. When a Yankee is used in conjunction with a suction pressure roll, the Yankee needs to be precisely crowned at the prevailing load to obtain a uniform nip. This procedure is necessary due to the inflexibility of the suction pressure roll arrangement and also due to loading at only the ends of the suction pressure roll. For the case of a shoe press, loading occurs at multiple points across the cross machine direction; individual shoe elements can be installed across the machine to give more precise cross machine direction pressing flexibility; and the shoe press is flexible and capable of conforming to the Yankee dryer surface. As a result, the precision to which the Yankee is ground for crowning will be less.

Figure 6 shows a schematic sketch of a typical pressure distribution curve for a suction pressure roll described by symmetrical mathematical functions like the sine and haversine curves. Since the nip pressure is relieved when the nip diverges, rewet is exacerbated for the suction pressure roll. Figure 7 shows a schematic sketch of a pressure distribution curve for a shoe press with a steep drop off where the felt is stripped from the sheet and later from the pressing blanket. Such a steep drop-off in pressure reduces the amount of rewet. Figure 8 shows a schematic sketch of a pressure distribution curve for a shoe press with a steeper drop off and where suction occurs in the felt at the point of simultaneous separation of the felt, sheet, and blanket when the nip pressure reaches about zero. The negative pressure in the felt, when the blanket and felt are stripped apart, is caused by capillary forces and should aid in holding water in the felt and should help further dewater the web.

Previous shoe, belt or blanket, and felt designs in wide nip presses do not permit

5 optimum separation of these members. For instance, present designs allow for quick separation of the felt and blanket since the felt cannot "wrap" the unsupported blanket. But the drawback is that the felt stays in contact with the sheet allowing capillary flow back into the sheet, i.e., rewet (see Figure 9). Figure 9 is a schematic sketch of a shoe press nip showing sheet, felt, and blanket. Point A in Figure 9 is the point of zero  
10 pressure on the pressure distribution curve at the exit side of the nip.

Rewet is determined in the literature by plotting moisture ratio versus the reciprocal of the basis weight using the following equation:

$$K_p = K_o + R/W$$

15 where  $K_p$  is the moisture ratio of the paper after the wet press in grams of water per gram of fiber;  $K_o$  is the moisture ratio of paper for  $1/W = 0$ ;  $W$  is the basis weight in  $\text{g/m}^2$ ; and  $R$  is the magnitude of the rewet of paper in  $\text{g/m}^2$  and corresponds to the slope of the straight line used to fit moisture ratio versus reciprocal basis weight data. The  
20 aforementioned equation was first established by John Sweet. Data plotted according to the above equation is frequently referred to in the literature as a Sweet plot. The original work can be found in Sweet, J.S., Pulp and Paper Mag. Can., 62, No. 7: T267 (1961) and a review article can be found in Heller, H., MacGregor, M., and Bliesner, W., Paper Technology and Industry, p.154, June, 1975. Rewet is much more significant for  
25 lightweight tissue grades than heavy weight linerboard grades. Rewet has been estimated to be from 5 to 50  $\text{g/m}^2$  of water, depending on the felt, furnish, etc. Rewet for a conventional shoe press can be determined from the above equation. The amount of rewet for the optimum shoe press is preferably less than about 50 % of the

5 amount determined from Sweet's theory using a conventional shoe press system. Rewet is preferably from 0 to 10 g/m<sup>2</sup> of water, more preferably from 0 to 5 g/m<sup>2</sup> of water.

10 According to another embodiment of the present invention, a pressing felt wraps the blanket and, therefore, pulls away quickly from the sheet reducing the time for possible rewetting. This design, as depicted in Figure 10, can be achieved by altering the take-away angle of the felt from the nip and tapering the exit side of the shoe. To aid in blanket deflection from the felt at the exit side of the shoe, the blanket diameter can be reduced; the blanket can be eccentrically arranged with respects to the press plane; or a roll (not shown in Figure 10) positioned against the blanket can deflect the belt further.

15 Figure 11 shows another embodiment according to the present invention. In Figure 11, a schematic sketch of a shoe press showing a sheet, felt, and blanket is displayed. This shoe press utilizes a very steep pressure drop at and following the exit of a nip curve of the press while simultaneously, separating the felt from the blanket and from the sheet. In this manner, the negative pressure generated by surface tension forces as the felt and blanket separate are effective in reducing the flow of water back into the sheet as the felt and sheet are separated. The drawing shows a sharp drop off of the blanket near the shoe which in turn permits a quick separation of the felt from both the blanket and the sheet. The outgoing felt would be pulled at an angle that equally bisected the Yankee and blanket surfaces. Then by adjusting the tension on the felt, the exact point of separation can be controlled to affect the minimum

20

25

5 in rewet. A felt drive roll located immediately following the shoe press can control the tension level on the felt. The objective of this embodiment according to the present invention is to affect the transfer of the sheet from the felt at the same time that the negative pulse caused by the separation of the felt and blanket occurs. This design not only minimizes the time the felt is in contact with the sheet; the added vacuum pulse will  
10 significantly reduce the amount of water that can flow, even over the short time. Point A in Figure 11 is the point of zero pressure on the pressure distribution curve at the exit side of the nip. The nip pressure curve for the sheet/felt in Figure 11 would most likely approach that shown in Figure 8.

The web is preferably either adhered to the Yankee dryer by nip transfer with a pressing unit including a pressing blanket or is after pressing adhered to the Yankee dryer. The web is dried by steam and hot air impingement hoods. Any suitable art recognized adhesive might be used on the Yankee dryer. Preferred adhesives include polyvinyl alcohol with suitable plasticizers, glyoxylated polyacrylamide with or without polyvinyl alcohol, and polyamide epichlorohydrin resins such as Quacoat A-252  
15 (QA252), Betzcreplus 97 (Betz+97) and Calgon 675 B. Suitable adhesives are widely described in the patent literature. A comprehensive but non-exhaustive list includes U.S. Patent Nos. 5,246,544; 4,304,625; 4,064,213; 3,926,716; 4,501,640; 4,528,316; 4,788,243; 4,883,564; 4,684,439; 5,326,434; 4,886,579; 5,374,334; 4,440,898; 5,382,323; 4,094,718; 5,025,046; and 5,281,307. Typical release agents can be used  
20 in accordance with the present invention.

The final product may be calendered or uncalendered and is usually reeled to



5           await further converting processes. The products according to the present invention may be subjected to any art recognized converting operations, including embossing, printing, etc.

The following example is illustrative of the invention embodied herein.

10

#### EXAMPLE 1

15

20

25

A nascent web was formed on a Crescent-forming machine using a blend of 50/50 long fiber/short fiber refined to 23° SR freeness. Chemicals like wet strength agents or dry strength agents were not added to the stock. The basis weight of the sheet on the Yankee dryer was 8.5 lbs/3000 ft<sup>2</sup>. Two pressing arrangements were used on the paper machine. In the first pressing arrangement, the sheet was pressed onto a Yankee dryer with a suction pressure roll. The vacuum in the suction roll was nominally 0.22 bar. In the second pressing arrangement, the suction pressure roll was replaced by a Yankee shoe press. The sheet was conditioned before the shoe press with a suction turning roll having the same size and open area as the suction pressure roll. The suction turning roll vacuum was nominally equivalent to the level used during the suction pressure roll experiments. After sheet conditioning, the web was pressed onto the Yankee with a shoe press. In order to obtain precise sheet solids data after the shoe press or the suction pressure roll, the Yankee dryer was run cold. Blotters were used to collect flatsheets for physical property determination. Two types of shoes were run: a typical 120 mm shoe and a 50 mm shoe. Figure 3 shows the pressure distribution of the shoes and the suction pressure roll. Figure 12 depicts a plot of sheet

solids versus line loading. The typical 120 mm shoe shows no solids benefit versus the suction pressure roll at present operating line load limits of current Yankee dryers (i.e., approximately, 87.5 kN/m), while the 50 mm pressure optimized shoe press shows an advantage of several percentage points of solids. Furthermore, the strength and specific volume properties of a web made with the 50 mm pressure optimized shoe press were equivalent to the strength and specific volume properties of a web made by the suction pressure roll.

Figures 13-15 illustrate a method for maximizing water removal in a press nip in accordance with another embodiment of the present invention. The present embodiment involves a conventional wet pressing (CWP) process. For consistency, like numbers have been used to indicate the corresponding portions of the apparatus depicted in Figures 13-15 with those of Figures 1-12. The description of the apparatus of Figures 1-12 thus applies equally to this embodiment, unless stated otherwise.

Referring to Figure 13, the present embodiment uses a shoe press, preferably a controlled crown roll with a flexible shell and a concave shoe hydrodynamically loaded against one another. The present embodiment further includes a belt or blanket (100) having a void volume that enhances sheet solids after the shoe press to further improve water removal in the press nip. Appropriate void volume can be achieved by a number of blanket configurations, including, but not limited to, those made by grooving, blind drilling and the like. The total void volume of the belt or blanket for use according to the present invention is preferably about 50 to about 3000 cm<sup>3</sup>/m<sup>2</sup>, more preferably about 100 to about 1000 cm<sup>3</sup>/m<sup>2</sup>, most preferably from about 200 to about 500 cm<sup>3</sup>/m<sup>2</sup>.

5

Blankets for use according to the present invention can include any art recognized blanket having, or which can be modified to have, the required void volume.

10

For example, blankets disclosed by E.J. Justus and D. Cronin in Tappi, August 1964, Vol. 47, No. 8, p. 493, which is incorporated herein by reference, include grooved belts that improve water removal in a press nip where the groove width is about 0.01 to about 0.03 in., the land width is about 2 to about 20 times the groove width and the groove depth is about 2 to about 10 times the groove width.

15

For another example, blankets disclosed by Bo-Christer Aberg in Das Papier No.6, 1996, which is incorporated herein by reference, include grooved belts that work at higher line loads and machine speeds than smooth belts. The belts have groove widths of about 0.5 to about 1 mm and a void volume of about 100 cc/m<sup>2</sup> to about 500 cc/m<sup>2</sup>.

20

For yet another example, blankets disclosed by P. Slater and K. Fitzpatrick in the 84<sup>th</sup> Annual Meeting of the Technical Section, CPPA, January 1998, which is incorporated herein by reference, include grooved belts that provide a press dryness about 1% to about 3% greater than the press dryness obtained with a similar smooth belt. The belts have groove widths of about 0.58 to about 0.79 mm and a void volume of about 200 cc/m<sup>2</sup> to about 365 cc/m<sup>2</sup>.

25

For still another example, blankets disclosed by D. Madden et al. in the Tappi 1998 Engineering Conference, which is incorporated herein by reference, include grooved belts that provide a press dryness about 1% greater than the dryness obtained with a blind drilled belt. The grooved belt has an open area of about a 20.3% and a

5 void volume of about 260 cc/m<sup>2</sup>, and the blind drilled belt has an open area of about 21% and a void volume of about 380 cc/m<sup>2</sup> void volume.

Referring to Figure 14, blind drilling involves drilling holes into a smooth blanket, as will be understood by one of skill in the art. Nip compression between a blind drilled blanket and the felt causes a hydraulic pressure gradient between the holes in the blanket and the felt which improves water flow and removal.

10 The blind drilled blanket preferably has a plurality of holes sequentially arranged in the machine direction and a plurality of rows sequentially arranged in the cross-machine direction to cause a hydraulic pressure gradient. The blind drilled blanket can take a variety of configurations. For example, the hole depth, hole diameter, hole spacing, hole angle, hole geometry, row spacing and/or row pattern can be varied.

In particular, the hole depth can range from about 0.2 to about 10 mm, more preferably about 0.5 to about 5 mm, most preferably from about 0.5 to about 3 mm. Also, the hole depth can extend partially or completely through the blanket.

The hole diameter can range from about 0.2 to about 10 mm, more preferably about 0.5 to about 5 mm, most preferably from about 1 to about 3 mm.

The hole spacing can range from about 1 to about 20 mm between holes arranged within the same row, more preferably about 1 to about 10 mm, most preferably from about 1 to about 5 mm.

20 The hole angle (i.e., the angle measured from the surface of the belt material counterclockwise to the side of the hole) can range from about 45 to about 135 degrees along any wall in either the machine or cross-machine, more preferably about 70 to

5 about 110 degrees, most preferably from about 80 to about 100 degrees.

The row spacing can range from about 1 to about 20 mm, more preferably about 1 to about 10 mm, most preferably from about 1 to about 5 mm.

10 The hole geometry can be curved, linear or curvilinear, e.g. round, square, elliptical, polygonal, and the row pattern can be such that the holes in each row are aligned in the cross-machine direction, offset in the cross-machine direction, aligned in the machine direction, offset in the machine direction and the like.

15 There is no requirement that all holes have the same configuration, rather, each of the holes can have a different configuration, or one or more individual or set of holes can have the same configuration as one or more other individual or set of holes. Further, there is no requirement that the hole pattern form any type of geometric or other pattern, for example, the pattern can be random.

20 Referring to Figure 15, forming grooves in the blanket involves removing elongated sections, as will be understood by one of skill in the art. Nip compression of the grooved blanket and the press felt causes a hydraulic pressure gradient in the machine direction, which improves water flow and removal.

25 The grooved blanket preferably has a plurality of grooved sections sequentially arranged in the cross-machine direction that circumscribe the blanket to cause machine direction water movement. The grooved blanket can take a variety of configurations. For example, the groove depth, groove width, groove bevel, groove angle, land width, open area and groove pattern can all be varied.

In particular, the groove depth can range from about 0.1 to about 8 mm, more

5 preferably about 0.2 to about 5 mm, most preferably from about 0.4 to about 3mm.

The groove width can range from about 0.1 to about 6 mm, more preferably about 0.2 to about 4 mm, most preferably from about 0.4 to about 3 mm.

10 The groove bevel (i.e., the angle measured from the surface of the belt material counterclockwise to the side of the groove minus 90°) can range from about 0 to about 45°, more preferably about 0 to about 30°, most preferably from about 0 to about 20°.

The groove angle can range from about 45 to about 135 degrees (with 90 degrees being orthogonal to the cross-machine direction), more preferably about 65 to about 115°, most preferably from about 80 to about 100°.

15 The land width can range from about 0.2 to about 25 mm, more preferably about 0.4 to about 10 mm, most preferably from about 0.6 to about 4 mm.

The open area can range up to 80% of the total blanket area, more preferably about 15 to about 50%, most preferably from about 20 to about 40%.

20 The groove pattern can be such that the grooves in each row are aligned in the cross-machine direction, offset in the cross-machine direction, aligned in the machine direction, offset in the machine direction and the like. Also, for blankets for use in the present invention, grooves need not have the same configuration, rather, all the grooves can have a different configuration, or one or more individual or set of grooves can have the same configuration as one or more other individual or set of grooves. Further, there is no requirement that the groove pattern form any type of geometric or  
25 other pattern, for example, the groove placement can also be random.

Blankets having the disclosed void volume will be readily apparent to the skilled

5 artisan. Such blankets can include any physical arrangement as long as the void space requirements are satisfied. Blankets for use in the present invention may be manufactured by any art recognized process, including but not limited to, casting molding, laser engraving, etc.

## 10 EXAMPLE 2

A punch press was used to perform dewatering experiments with different belt structures. An AMFlex 3S felt manufactured by Appleton Mills Corporation was used to dewater the paper web. The web basis weight was 8.9 lbs/rm. The felt dryness was controlled to 69.3% dryness by using blotters and a couch roll to remove excess water. Web moisture was controlled to 19.3% dryness by rewetting moist webs using a water spray. The webs were made from a 50/50 blend of northern softwood kraft and eucalyptus refined in a PFI mill to 510 ml CSF.

15 A smooth belt, a blind drilled belt and a grooved belt were used in the punch press experiment. The blind drilled belt had a bore area of 3.82 mm<sup>2</sup>, a bore depth of 1.76 mm, an open area of 22.73% and a void volume of 402.9 cc/m<sup>2</sup>. The grooved belt had a groove width of 0.66 mm, a groove depth of 1.41 mm, a pitch of 0.33 grooves/mm, an open area of 21.78%, and a void volume of 270.6 cc/m<sup>2</sup>.

20 The punch press was operated such that the average nip pressure was fixed at 400 psi and the average nip dwell time was fixed at 1.8 ms. The experimental post press dryness results for the experiment were:

smooth belt 31.0 +/- 0.30%

5                      blind drilled belt      39.2 +/- 0.28%

                        grooved belt              40.3 +/- 0.42%

with the +/- percentage being the 95% confidence limit for the test.

10                      These results indicate that pressing with either a blind drilled or grooved belt leads to enhanced sheet solids when compared to a smooth belt. These results also indicate that pressing with a grooved belt leads to enhanced sheet solids over a blind drilled belt.

Other embodiments of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and examples be considered as exemplary only, with the true scope and spirit of the invention being indicated by the following claims.